

FULL AUTOMATIC RIGID BOX MAKING MACHINE

1

Specifications:			
Cover Paper size		Width:155-560	Length:190-660
BOX SIZE	L(mm)	85-400mm	
	W(mm)	60-300mm	
	H(mm)	15-125mm	
Ear folding(mm) :		15 -100	
Speed (Po	cs/min)	15-35	
Turn in depth (mm)		15-70	
Paper wrap Grammage:		100-350g/m2	
Cardboard blank thickness:		0.8-3mm	
Power:380V/50Hz		Electrical power:24KW	
Glue tank capacity:45L		Precision error: ±0.05mm	
Paper pile height:260mm		Air supply:410L/min 0.6MPA	
Cardboard pile height:1000mm			
Net weight: 8100KG			
Overall dimension:		6800X4300X3000)mm

Note: 1.The box length less than 125mm needs to add small specifications accessories;

- 2. The size of the box is restricted by the size of the cover paper;
- 3.Online viscometer system(optional);
- 4. The company does not provide air compressors;
- 5. Several factors that affect the speed of the machine: raw materials, glue and operator proficiency;
- 6.Due to continuous innovation in product design, the above data is for reference only; and are subject to change without notice.

> Features

- 1. Suitable for all kinds of automatic rigid box production line.
- 2. Automatic suction and conveying of paper and cardboard.
- 3. Full computer function parameter setting and fault alarm function.
- 4. The whole machine adopts the control system of the motion controller, and touch screen man-machine interface control system.
- 5. Taping machine using separate man-machine interface control system.
- 6. Electronic cam and mechanical cam combine to play their respective advantages.
- 7.24-hour control glue preheating function, glue viscosity automatic control system (optional)

Sample Box:

