



印策（上海）贸易有限公司
INCHO (SHANGHAI) TRADING CO., LTD



LAMINATING MACHINE YDFM-A



YDFM-A series manual laminating machine is a kind of multi-functional laminator which is newly developed upon long time of users' feedback and market needs. It suits the lamination of pre-glued film and glueless film. Glueless film lamination means the machine laminates the glueless film without any glue on paper directly in a certain temperature and pressure. This technology is a new green lamination. The whole process has no any glue thereof, and reduces energy-loss and saves production costs, and also avoids environmental pollution and toxic residuum from traditional laminating technology. The laminated products will be water-proof, durable, of clear picture and good spatial effect. And the machine is widely used for the lamination of packing materials, labels, books, drawings and maps etc.

Features: It is used for the lamination of pre-glued film (also named thermal film) and glueless film

- SCHNEIDER frequency converter is equipped for infinitely variable speed, and the operator can change the machine's speed easily and guarantee the machine's running stable.
- One-piece construction design makes the machine run more stably, and lengthens the machine's lifetime.
- Manual paper feeding.
- Magnetic regulating plate can be adjusted easily to regulate manual paper feeding.
- High precision of chrome plated heating roller is equipped with built-in oil heating system, which has excellent performance to temperature control. The laminating temperature is adjustable upon applications.
- Hydraulic pressuring system provides big and steady pressure to guarantee good laminating quality.
- Film cutter cuts film width to make it meet paper size. The cut film is left on the film release spindle.
- Film perforating wheel perforates film edge to make the separation of laminated paper easy.
- Laminated paper is rolled up automatically by the winding spindle. Winding speed is adjustable upon requests. Winded paper will be cut by manual work.

Technical Parameters

Model	YDFM-720A	YDFM-920A	YDFM-1050A
Max Laminating Width	680mm	880mm	1040mm
Laminating Speed	0-30 m/min	0-30 m/min	0-30 m/min
Laminating Temperature	≤130℃	≤130℃	≤130℃



印策（上海）贸易有限公司
INCHO (SHANGHAI) TRADING CO., LTD

Paper Thickness	125-500g/m ²	125-500g/m ²	125-500g/m ²
Gross Power	13kw	15kw	16kw
Total Weight	600kg	700kg	900kg
Overall Dimensions	1900*1500*1550mm	1900*1700*1550mm	1900*1900*1550mm